

Crescent Infrared Transmitter IRT-30



Crescent infrared transmitter/microphone with rechargeable NiMH batteries and included PM-500 Plug-in microphone

Specifications

Transmission Carrier	Infrared
Transmission Frequencies	2.08 MHz & 2.54 MHz
Channel Switchable A or B	Field Switchable
Transmitting Diodes	Six
Modulation	FM Wide-Band
Pilotone Frequency	32.768 KHz
Peak Deviation	± 25KHz
Operating Range	1500 Ft ² . 60 Ft.
Power Switch (Push)	On/Off—Mute
Battery Charge Level (LED)	Green, (Useable Charge) Red, (Needs Charging)
Battery Life	Approx. 7 Hr./Charge
Transmission Angle	180° Conical
User Controls	Mic Volume—Rotary, Power on/off, mute momentary, Ch. Select (A or B)
External Mic./Aux Input	3.5mm Switchable, Mic or Line
Dimensions	4¾" W x 1" D x 1¾" H
Weight	3.0 oz. w/ Battery

Features

- Stylish design
- Lightweight, only 3 oz. w/ battery
- Comfortable to wear
- Snap-in lanyard attach (breakaway safety)
- Push "on/off" power button
- Battery level indicator—LED
- Push "on/off" mute button
- Blinking LED in mute mode
- External input jack (3.5mm), switchable: Mic. or Aux. level
- Channel "A" or "B" selectable
- Volume control, Rotary
- Single "AA", Duracell battery, rechargeable NiMH
- External contacts for drop-in charger
- Included PM-500 Plug-in microphone