

Pendant Infrared Transmitter IRT-89



Pendant infrared transmitter/microphone with rechargeable NiMH batteries and included LM-300 Plug-In unidirectional microphone for true voice reproduction and excellent feedback suppression

Specifications

| | |
|----------------------------|--|
| Transmission Carrier | Infrared |
| Transmission Frequencies | 2.08 MHz & 2.54 MHz |
| Channel Switchable A or B | Field Switchable |
| Transmitting Diodes | Ten |
| Modulation | FM Wide-Band |
| Pilotone Frequency | 32.768 KHz |
| Peak Deviation | ± 25KHz |
| Operating Range | 2500 Ft ² . 60 Ft. |
| Power Switch (Slide) | On/Off |
| Battery Charge Level (LED) | Green, (Useable Charge) Red, (Needs Charging) |
| Battery Life | Approx. 7 Hr./Charge |
| Transmission Angle | 180° |
| User Controls | Mic. Volume Power On/Off CH. Select (A or B) |
| External Mic. Input | Lo-z, 3.5mm |
| Lanyard | Heavy Spring Wire |
| Dimensions | 5¼" H x 1½" W x ¾" D |
| Weight | 4.6 oz. w/ Batteries |

Features

- Small/lightweight (4.6 oz..)
- Ten emitting diodes (broad/powerful IR Output)
- Internal microphone
- Mic. input (top/center) for external microphone
- Volume control, Rotary
- Power "on/off" switch
- Battery level indicator—LED
- Channel "A" or "B" selectable
- Two "AA", Duracell, rechargeable NiMH batteries
- External contacts for drop-in charger
- Clip with lanyard
- Included LM-300 Plug-In unidirectional microphone for true voice reproduction and excellent feedback suppression