

# Wall-Mount Speaker SP-2000



SP-2000 Wall-mount/book shelf speaker, two-way, 8  $\Omega$ , mounting bracket. White.

## Specifications

|                        |  |
|------------------------|--|
| Frequency Range        | 80 Hz to 16 kHz, $\pm$ 6dB                                 |
| Power                  | 30 watts Continuous  |
| Sensitivity            | 88 dB SPL  |
| Impedance              | 8 $\Omega$   |
| Crossover Frequency:   | 6 kHz  |
| Nominal Coverage       | 90° x 90°  |
| LF Driver              | (5.25 in) Polycarbonate / rubber                           |
| HF Driver              | High efficient 1" Mylar domed tweeter                      |
| Enclosure Material     | Structural reinforced ABS enclosure with metal mesh grille |
| Termination            | Spring terminal for secure speaker wire connection         |
| Dimensions (H x W x D) | 5.5 x 7.25 x 4.25 in                                       |
| Net Weight (ea)        | 5 lbs 2 oz   |
| Shipping Weight (pr)   | 10 lbs 9 oz  |
| Included Accessories   | Wall mount bracket   |

## Features

- Two-way speaker,
  - 6" woofer and a high efficient 1" mylar domed tweeter
  - Passive crossover
  - Housed in a ported enclosure
  - Shielded magnet to prevent video interference
- Frequency Response: 80 Hz–16,000 Hz,  $\pm$  6dB
- Impedance: 8  $\Omega$
- Power Handling: 30 watts Continuous
- Structural reinforced ABS enclosure with metal mesh grille
- Mounting bracket for wall-mount or desk top stance
- Screw terminal for secure speaker wire connection
- White Color